



Award Winning True RMS Clamp Meter

New Feature!

- Measure Power Factor quickly and easily.
- Read Active Power (W), Apparent Power (VA) & Reactive Power (VAR)

We Made It Better!

- Magnetic hanger strap with flexible application
- Easy access battery latches. No screwdriver needed.
- Test lead storage for convenience
- Automatic AC/DC selection for Volts and Amps
- Added selection dial to navigate test functions
- Increased range of Volts and Capacitance
- Back probes included for mini-split applications



All The Pro Features You Love

- Same functionality as our popular DL429B
- 13 Key test functions
- More than 15 features
- Wireless to a Free App

Plus, Motor Tests!

- **3-Phase Motor Rotation Test** to confirm motor direction
- **Unbalanced Motor Test** to determine a motor's load efficiency
- **Low Pass Filter** to screen out unwanted higher frequencies from Variable Frequency Drives

Distinguished In The Marketplace

- 2-Year Limited Warranty
- Professional Safety Ratings

Available For A Great Price!

\$319⁹⁵ TNP





BACKED BY
UEI
QUALITY

2
YEAR
WARRANTY



DL500 Series Clamp Meter Comparison



Part #	DL569	DL579	DL589	DL599
UPC	053533509281	053533509274	053533509144	053533509137
TRMS		•	•	•
AC Volts	750V	750V	750V	1000V
DC Volts	1000V	1000V	1000V	1000V
AC current (amps)	400A	600A	600A	600A
DC current (amps)			600A	600A
Resistance (Ohms)	40kΩ	60MΩ	60MΩ	60MΩ
Continuity/Diode	•	•	•	•
Capacitance (Farads)	4000μF	6000μF	2000μF	9999μF
AC / DC microamps	2000μA	2000μA	2000μA	2000μA DC
Frequency (Hertz)		99.99Hz - 99.99kHz	99.99Hz - 99.99kHz	99.99Hz - 99.99kHz
Duty cycle		•	•	•
Low Z (impedance)		•	•	•
LRA inrush		•	•	•
Temperature (K-type input)		-328° to 2462°F	-328° to 2462°F	-328° to 2462°F
NCV (LED & Audible)		•	•	•
Min/Max	•	•	•	•
Hold	•	•	Peak Hold	Data/Peak
Ranging	Auto	Auto/Man	Auto/Man	Auto/Man
Auto off & Low Battery	•	•	•	•
Test lead storage	•	•	•	•
Dual display	•	•	•	•
High voltage alert	•	•	•	•
Auto Calibration	•	•	•	•
Easy access battery latches	•	•	•	•
Backlight		•	•	•
Magnetic mount/strap		•	•	•
Worklight			•	•
Temperature differential			•	•
DC Zero			•	•
Auto AC/DC selection for V/A				•
Wireless to app				•
Power Factor				•
Active(W), Apparent(VA) & Reactive(VAr) Power				•
3-Phase motor rotation test				•
Motor unbalanced test				•
Low pass filter				•
Safety Rating	CATIV 300V CATIII 600V	CATIV 600V CATIII 1000V	CATIV 600V CATIII 1000V	CATIV 600V CATIII 1000V
Warranty	1-year limited	1-year limited	2-year limited	2-year limited

Safety Rated: CATIV 600V / CATIII 1000V
Certified by ETL to IEC 61010-1, 3rd edition



Includes

- Silicone Test Leads (ATL58)
- Back Probes (APB3)
- Alligator Clips (AAC3)
- Temperature Probes 2 (ATT29)
- Zippered Pouch
- Batteries 4 (AAA)
- Manual

DL599 Replaces Previous Models

- DL419
- DL429B
- DL429