



Infrared Thermometer w/ Circular Laser Targeting



Functions

- Temperature range:
-76° to 1022°F
(-60° to 550°C)
- 12:1 Distance-to-spot ratio

Features

- Circular laser targeting
- Protective rubber grip
- Max value capture
- Selectable emissivity: 0.95 or 0.70
- Auto power off
- 1-Year limited warranty

Includes

- Holster/pouch
- Batteries (AAA) 2
- Manual (17300)



Applications

- Check register temperatures
- Hard to reach registers and appliances
- Faulty breakers and panels
- Motors, fans or other moving parts
- Boilers, hanging heaters and radiators
- Troubleshoot hydronic systems

Specifications

Temperature Range	-76° to 1022°F (-60° to 550°C)
Operating Temperature	32° to 122°F (0° to 50°C)
Accuracy (Tobj=15-35°C, Tamb=25°C)	± 2.7°F (1.5°C)
Accuracy (Tamb=23 ± 3°C)	Tobj=0-550°C: ±2% of reading or 2°C(4°F) whichever is greater Tobj=-60-0°C: ±(2°C+0.05/degree C)
Emissivity	0.95 or 0.70 (0.95 is default)
Resolution	0.1°C/0.1°F at -76.0 to 999.9(°C/°F), otherwise 1°C/1°F
Response Time	1 sec.
Distance-to-Spot Ratio	12:1
Dimension	6.43" x 4.62" x 1.92" (163.4 x 117.5 x 48.8 mm)
Weight	7.87 oz (223g) including batteries

Downloads



Manual



Data Sheet

H26-252



0 53533 50741 6

Made in CHINA