

UEI DCM3

TEST INSTRUMENTS™ Capacitance Meter

NEW WIDE RANGE WITH PROFESSIONAL RESOLUTION

- 9 Ranges!
- 200 pF to 20 mF (20,000 μ F)
- Zero adjustment
- OVER RANGE indicator
- Polarity indicator
- Quick display refresh rate
- Fuse protected input



DCM3 • Capacitance Meter

The DCM3 Digital Capacitance Meter offers solid value in an industrial quality meter. The wide range of inputs allows testing from the smallest electronic components to large run/start capacitors. The rugged design with protective boot and auto power off function keep your meter working under the toughest work conditions.

The DCM3 has the following features:

- 9 Ranges!
- 200 pF to 20 mF (20,000 μ F)
- Zero adjustment (± 20 pF for compensation of the measuring leads)
- Over range indication
- Polarity indicator
- Display refresh rate 2.5/sec.
- Auto off
- Low battery indication
- 3.5 digit LCD display 1999/ count
- Fuse protected input


Specifications

Range	Resolution	Accuracy	Test Frequency
200 pF	0.1 pF	$\pm 1\%$ reading +3 dgt	820 Hz
2000 pF	1 pF		
20 nF	10 pF		
200 nF	100 pF		
2 μ F	1 nF		
20 μ F	10 nF	82 Hz	8.2 Hz
200 μ F	100 nF		
2000 μ F	1 μ F		
20 mF	10 μ F	$\pm 2\%$ reading +3 dgt	
		$\pm 4\%$ reading +9 dgt	

Test Voltage: L3.5V
 Input protection: 0.25A/250V
 Battery: 9V (NEDA 1.604)

Abbreviation	Description	Multiplier	Description
pF		10^{-12}	.000000000001
nF		10^{-9}	.000000001
μ F*		10^{-6}	.000001
mF		10^{-3}	.001

*On some capacitors, the prefix for microfarads (μ F) may be labeled MF. This is the equivalent of the μ F ranges on this meter.



Distributed By:



1-800-547-5740 • Fax: (503) 643-6322
 www.ueitest.com • Email: info@ueitest.com

IN CANADA
 Phone: 1-877-475-0648 • Fax: (604) 278-8299
 www.ueitest.com • Email: infocanada@ueitest.com

IN EUROPE
 Phone: +44 1707 375550 • Fax: +44 1707 393277

