



Digital Micron Gauge



Functions

- Vacuum range: 0 to 25,000 Microns
- 1 Micron resolution at $\pm 5\%$ accuracy

Features

- Vacuum leak rate indicator
- Ambient temperature display
- Programmable for both target vacuum level and elapsed time
- High pressure indication
- Sleep mode
- Auto power off
- Oil contamination sensor
- Selectable units
- Analog level bargraph
- Calibration test mode
- User calibration
- 1-Year limited warranty

Includes

- Battery (9V)
- Removable swivel hook
- 45° Brass adapter
- Manual

Applications

Real time system analysis
 Current, real time vacuum readings
 Determine proper levels of vacuum in HVAC systems

Specifications

Range	0 – 25,000 Microns (3333 Pa, 33.330 mBar, 25,000 mTorr, 25.000 mmHg)
Vacuum Accuracy	5% of Reading \pm 5 Microns
Vacuum Resolution	1 Micron > 10,000 Microns 0.1 Micron < 10,000 Microns
Warm Up Time	Instant
Response Time	Instant
Power	9V Alkaline Battery
Battery Life	Up to 300 hours
Operating Temperature	10°F – 122°F (-12°C – 50°C)
Dimensions	3" x 3.5" x 1.25"
Weight	6 oz. (170g) including Battery

Downloads



Manual



Data Sheet

H27-265



Made in USA