



Key Selling Points



Wireless Pressure Probe






WPP1 has a pivoting hinge to allow access to connections in tight spaces. The Pass-through fitting allows users to connect directly to the probe without additional adapters for a more efficient work flow, saving money on refrigerant and only bringing out the hoses when they're needed.

Temperature Pipe Clamp






The WPC1 is a thermistor pipe clamp that plugs into the Pressure probe to send its data to the App. The narrow jaw allows users to get onto narrow pipe lengths, while the over-molded texture provides a secure grip. The unique spring design allows for easier opening and closing without compromising its grasp of the pipe. The WPC1 is compliant to California's Title 24 standard.

Solid Connection Setting up probes in the App is quick and easy. Once a probe is assigned to a part of the system, it will automatically reassign that probe each time the App is launched. The latest wireless technology allows up to 150 ft. connectivity range pending environmental conditions and if the connection drops, the probe will automatically reconnect to the App.

UEi HUB App The UEi HUB App shows a system's Liquid and Suction measurements and calculations in an intuitive easy-to-read display. Users can easily select from over 44 refrigerants as well as add or subtract favorites. The user-friendly navigation bar allows users to quickly change units, reassign probes or get support from the manual, web support or UEi's customer service.



Competitive Comparison

Wireless Probe Kits					
	UEi	Yellow Jacket	Parker/Sporian	Testo	Fieldpiece
	HUB4	67002	953495	0563 0002	JL3KR4
					
Pressure Probes Included	2	2	2	2	2
Pipe Clamps Included	2	2	2	2	2
Wireless Type	BLE 4.2	BLE 4.0	BLE 4.0	BLE 4.0	BLE 4.0
Wireless Range	150 ft	400 ft	Not listed	50 ft	350 ft
Thermistor Pipe Clamp	•	•	•	•	
Temp Range	32°F to 176°F	-40°F to 266°F	-40°F to 250°F	-40 to 302°F	-50°F to 257°F
Pressure Range	0 to 750 psig	0 to 700 psia	0 to 700 psig	-15 to 875 psi	0 to 580 psig
Accuracy	.5% F.S.	0.5% F.S.	.75% F.S.	.5% F.S.	±1 or 2 psig
Pass Through Port (no adapters or hoses)	•	•	•		
Pivoting Hinge Design	•				
Carrying Case	•	•	•	•	•
Warranty	1 year	2 year	NA	2 year	1 year
TNP	\$399.95	\$610.00	\$432.95	\$266.00	\$380.00



Download this competitive comparison here.

Competitive product functionality, features, accessories and pricing are based on public information available at time of publication and subject to change without notice. Competitive brands and images are property of their respective owners.

WWW.UEITEST.COM

Copyright ©2018 Kane USA Inc. All Rights Reserved. L462
IOS® and Android™ are property of their respective owners.

USA **1.800.547.5740**
CANADA **1.877.475.0648**