



### Key Selling Points

#### Detects industry standard refrigerants

The RLD15B is designed and certified to meet the new, tougher standards and detects the latest refrigerants.

#### Digital numeric leak size indicator

The RLD15B is equipped with a heated sensor to increase accuracy and features a digital leak size indicator.

#### Essential features and functions

The RLD15B has all the same functions as the RLD15 and includes 3 sensitivity levels, a visual leak detector and adds a worklight.

### Competitive Comparison

Digital Manometers					
Brand	UEI	Fieldpiece	Testo	Amprobe	Supco
Model #	RLD15B	SRL8	316-3	RLD-1	HLD200
Sensitivity	.05 oz/yr	0.6 oz/yr	0.15 oz/yr	0.5 oz/yr	0.1 oz/yr
Sensitivity levels	3	3	2	3	5
Sensor life	>300 hrs	5 yrs	<100 hrs		
Replaceable sensor	•	•	•	•	•
LED warning	3	8	4	3	7
Audible alarm	•	•	•	•	•
Response time	<1 sec	<1 sec			<1 sec
Probe length	17"	15"	11.2"	15.5"	12"
Numeric display	7 segment digital (1-9)				
Approx. size indications	1-3/<0.1 4-6/0.1 to 0.5 7-9/>0.5				
Warm up time	20 sec	30 sec	20 sec	45 sec	6 sec
Carrying case	•	•	•	•	•
Warranty	2-Year	1-Year	2-Year	1-Year	1-Year
T.N.P.	299.95	247.20	260.13	241.96	109.95

### Download this competitive comparison here.

Competitive product functionality, features, accessories and pricing are based on public information available at time of publication and subject to change without notice. Competitive brands and images are property of their respective owners.

