



### Key Selling Points

#### High-Capacity

The WRSX is a high-capacity refrigeration scale measuring loads up to 330 lbs. with uncompromising repeatability regardless of how centered the weight is on the measuring platform. The rechargeable batteries provide unprecedented performance needed for today's wirelessly connected equipment.

#### Smart Technology

The WRSX gives users the option to view readings on either the backlit display or a smart device. Using a free iOS® and Android™ App that offer a users an intuitive interface, easy connection, large digits, a programmable alarm and selectable measuring units. The WRSX also offer techs an extended wireless range to help reduce dropped connections.

#### Real-World Toughness

The dynamic body design is very durable and compact with an overload protection to withstand 150% of maximum load capacity.



### Competitive Comparison

| Refrigerant Scale Competitive Comparison                |   |  |  |
|---|---|--|--|
| Brand   | UEi   | UEi  | UEi  |
| Model #   | WRSX  | WRS220                                     | WRS110                                     |
|   |   |  |  |
| Capacity (Load cell)                                    | 330 lbs (150 kilograms)                               | 220 lbs (100 kilograms)                    | 110 lbs (50 kilograms)                     |
| Accuracy (between 68° to 122°F (20° to 50°C))           | 0 to 40g ±0.2% ±1 dgt or 0,25oz, whichever is greater | ±0.20% FS ±1 dgt                           | ±0.25% FS ±1 dgt                           |
| Accuracy (between 32° to 68°F (0° to 20°C))             |   | ±0.4% FS ±1 dgt                            | ±0.6% FS ±1 dgt                            |
| Resolution  | .25oz (7g)  | 0.2 oz (5g)                                | 0.1 oz (3g)                                |
| Operating range   | 32° to 140°F (0° to 60°C)                             | 32° to 158°F (0° to 70°C)                  | 32° to 158°F (0° to 70°C)                  |
| Programmable alarm (in App)                             | •   | •  | •  |
| English/metric scales                                   | •   | •  | •  |
| Display   | Backlit LCD and App                                   | in App                                     | in App                                     |
| Wireless  | •   | •  | •  |
| 35 ft to 100 ft wireless distance (pending environment) | •   | •  | •  |
| IP (of electronics)                                     | 55  | 55   | 55   |
| Free App  | •   | •  | •  |
| Large size platform (>10.5")                            | •   | •  | •  |
| No-slip rubberized pad                                  | •   | •  | •  |
| Weight  | 6.5 lbs   | 5.3 lbs                                    | 5.3 lbs                                    |
| Compact   | •   | •  | •  |
| Power   | Rechargeable Battery                                  | 9V   | 9V   |
| Battery life  | Min 100 hrs   | Min 40 hrs                                 | Min 40 hrs                                 |
| Dimensions  | 11" x 11"x 2.5" (27.9cm x 27.9cm x 6.35cm)            | 11" x 11"x 2.5" (27.9cm x 27.9cm x 6.35cm) | 11" x 11"x 2.5" (27.9cm x 27.9cm x 6.35cm) |



### Download this competitive comparison here.

Competitive product functionality, features, accessories and pricing are based on public information available at time of publication and subject to change without notice. Competitive brands and images are property of their respective owners.

Patent Pending